



FOLDABLE SOLUTION

"Double Wing" Enhanced Container Smart house







PRIMARY FEATURE LIST

Main Frame	Mid Roof beam	T2.0mm Q235B with galvanize
	Mid bottom beam	T2. 75mm Q235B
	Side End beam	T2.0mm Q235B with galvanize
	Neutral pillar	T2.0mm Q235B with galvanize
	Side wall frames	T2.0mm Q235B with galvanize
	Sub frames	T2.0mm Q235B with galvanize
	hanging head	T5. Omm Q235B
	fold hinges	40mm with galvanize
	Coating	Eco-friendly paint
	mid cabinet	80*100*2, 75
Pow Ton	side cabinet	40*60*2.0 thick square tube
	Exterior top	50EPS foam board
Box Top Wall	Interior top	V200 Inner Suspended Ceiling
	Side wing top insulation	65mm EPS board
	side wall Frt&Rr	65mm EPS board
Floor	Inside partitions	50mm EPS foam board
	mid floor	Fireproof glass magnesium flooring 17mm
F 1001	side floor	Fireproof glass magnesium flooring 17mm
Electrical System	Electrical wiring is installed in strict accordance with moisture-proof specifications, and all electrical products must comply with CE certification. Connect the circuit according to the circuit engineering specification, indoor: 4 ceiling lamps, 4 six-hole single-open sockets, 5 single-open sockets, 3 air-conditioning sockets, and 1 leakage protector.	
Gate/Door	aluminum door 1895*2235mm *1	
Window	aluminum window 930*1130mm *4	

SAMPLE ROOM - BATHROOM







SAMPLE ROOM - KITCHEN







SHIPMENT APPROACH





